

| Ref # | Hits | Search Query  | DBs   | Default Operator | Plurals | Time Stamp       |
|-------|------|---|---|------------------|---------|------------------|
| L2    | 4    | "439"/219,700,169,428.ccls. and PROBE WITH PIN AND SERIES AND COMPONENT and bias\$3 | US-PGPUB;<br>USPAT;<br>USOCR;<br>EPO; JPO;<br>DERWENT;<br>IBM_TDB | OR               | OFF     | 2005/11/22 15:05 |
| L3    | 2298 | "probe pin"   | US-PGPUB;<br>USPAT;<br>USOCR;<br>EPO; JPO;<br>DERWENT;<br>IBM_TDB | OR               | OFF     | 2005/11/22 15:01 |
| L4    | 44   | L3 and component and sleeve   | US-PGPUB;<br>USPAT;<br>USOCR;<br>EPO; JPO;<br>DERWENT;<br>IBM_TDB | OR               | OFF     | 2005/11/22 15:01 |
| L6    | 302  | I3 and (serial or series)   | US-PGPUB;<br>USPAT;<br>USOCR;<br>EPO; JPO;<br>DERWENT;<br>IBM_TDB | OR               | OFF     | 2005/11/22 15:02 |
| L7    | 82   | I3 and serial   | US-PGPUB;<br>USPAT;<br>USOCR;<br>EPO; JPO;<br>DERWENT;<br>IBM_TDB | OR               | OFF     | 2005/11/22 15:02 |
| L10   | 41   | 6 and capacitor   | US-PGPUB;<br>USPAT;<br>USOCR;<br>EPO; JPO;<br>DERWENT;<br>IBM_TDB | OR               | OFF     | 2005/11/22 15:06 |